



RAVENOL ATF+4 Fluid

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1211100

Oil type: Synthetic

Approvals: Chrysler License-No. 40630041 FCA US LLC

Recommendations: Chrysler MS-9602, Fiat 9.55550-AV4, Mopar 68218054GA, Mopar 68218057GA, Mopar 68218058GA

Application: Passenger car



RAVENOL ATF+4® Fluid is a synthetic, licensed automatic transmission fluid ATF with an unique additive package for Fiat-Chrysler, Jeep and Dodge automatic transmission.

RAVENOL ATF+4® Fluid guarantees maximum wear protection in all operating conditions.

RAVENOL ATF+4® Fluid is mixable with all ATF+4®, ATF+2® or ATF+3® transmission oil.

1L | 1211100-001

4L | 1211100-004

10L | 1211100-010

20L | 1211100-020

20L | 1211100-B20

60L | 1211100-060

208L | 1211100-208

Application instructions

RAVENOL ATF+4® Fluid is recommended for refilling and fill up automatic transmission oil for Fiat-Chrysler, Dodge, Plymouth, RAM, Jeep and Eagle vehicles with automatic transmission.

RAVENOL ATF+4® Fluid achieves the warranty of FCA US LLC (Fiat Chrysler Automobiles) and is released with License-No. 40630041.

RAVENOL ATF+4® Fluid meets the requirements of current and previous standards for Fiat-Chrysler, Dodge, Plymouth, Jeep and Eagle automatic transmission oil.

Characteristics

- Better protection and better performance than ATF+3®
- Extended transmission life
- Reduces maintenance costs
- Better shift quality through a consistent viscosity profile
- Better cold flow properties
- Smooth switching at low temperatures
- Less transmission wear when operating at low temperatures
- Better oxidation stability and thermal stability than the previous ATF+3®
- Longer oil life period
- Lower oil consumption
- Better fuel economy
- Longer oil change intervals (has been tested extensively with oil change intervals of about 160,000 km)

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		rot	VISUELL
Viscosity at 100 °C	mm ² /s	7,5	DIN 51659-2
Viscosity at 40 °C	mm ² /s	35,1	DIN 51659-2
Viscosity Index VI		192	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	6.500	ASTM D2983
Density at 20 °C	kg/m ³	845,0	EN ISO 12185
Flashpoint	°C	198	DIN EN ISO 2592
Pourpoint	°C	-63	DIN ISO 3016