



RAVENOL Low Emission Truck SAE 10W-40



Kategorie: Truck engine oil

Artikelnummer: 1122109

Viscosity: 10W-40

Specifications: ACEA E11, ACEA E4, ACEA E7, ACEA E8, ACEA E9, ACEA E6, API CJ-4, API CK-4

Oil type: Semi-synthetic

Approvals: DTFR 15C110, DTFR 15C120, Mack EO-O PP (Premium Plus), Renault Trucks RLD-3, VOLVO VDS-4

Recommendations: Caterpillar ECF-3, Cummins CES 20081, DAF, Detroit Diesel Corporation (DDC) DFS93K218, Deutz DQC IV-10 LA, DTFR 13D110 (MB 235.28), JASO DH-2, MAN M 3271-1, MAN M 3477, MAN M 3575, MB 228.31, MB 228.51, MB 235.28, MTU Typ 2.1, MTU Typ 3.1, Scania LowAsh, Voith Retarder B

Application: Agricultural machinery, Truck

1L | 1122109-001

5L | 1122109-005

10L | 1122109-010

20L | 1122109-020

20L | 1122109-B20

60L | 1122109-060

60L | 1122109-D60

208L | 1122109-208

208L | 1122109-D28

1000L | 1122109-700

RAVENOL Low Emission Truck SAE 10W-40 is an all-season semi-synthetic multigrade SHPD engine oil (Super High Performance Diesel), which has been developed to the exhaust emission standards Euro V and Euro VI and is used in extremely heavy duty commercial vehicle diesel engines.

RAVENOL Low Emission Truck SAE 10W-40 is suitable for application in exhaust-optimized engines with exhaust gas after treatment.

RAVENOL Low Emission Truck SAE 10W-40 reduces friction, wear and fuel consumption and provides for longer oil change intervals in turbo diesel engines.

RAVENOL Low Emission Truck SAE 10W-40 with shear stable additives improves performance, reliability and cleanliness of the engines.

Application instructions

RAVENOL Low Emission Truck SAE 10W-40 is a year round high performance motor oil, especially designed for economic use in Euro V and Euro VI engines with after treatment systems in the viscosity class SAE 10W -40 heavy duty vehicle diesel engines.

RAVENOL Low Emission Truck SAE 10W-40 is preferred recommended by the extended oil change intervals specified by the manufacturer in turbo diesel engines.

Characteristics

- An extremely high pressure absorption capacity
- Very high oxidation stability
- Excellent resistance to aging
- Excellent viscosity-temperature behavior
- High safety reserves even under boundary lubrication conditions
- Suitable for extended oil change intervals
- Best suitability for difficult operating conditions

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		braun	VISUELL
Sulphated Ash	%wt.	0,83	DIN 51575
tbh	mg KOH/g	9,2	ASTM D2896
Viscosity at 100 °C	mm ² /s	14,7	DIN 51659-2
Viscosity at 40 °C	mm ² /s	97,3	DIN 51659-2
Viscosity Index VI		157	DIN ISO 2909
CCS Viscosity at -25 °C	mPa*s	5933	ASTM D5293
Density at 20 °C	kg/m ³	859,0	EN ISO 12185
Flashpoint	°C	230	DIN EN ISO 2592
Pourpoint	°C	-39	DIN ISO 3016