



RAVENOL ATF M 9-Serie

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1211108

Oil type: Synthetic

Recommendations: MB 236.10 (A 001 989 21 03 10), MB 236.12 (A 001 989 45 03 10), MB 236.14 (A 001 989 68 03 10)

Application: Passenger car



RAVENOL ATF M-9 Serie is automatic transmission oil ATF, produced on the basis of high-quality hydrocrack oils with special additives and inhibition which guarantees a perfect function of the automatic transmission.

RAVENOL ATF M-9 Serie is one of the ATF (Automatic Transmission Fluid) of the newly developed generation for all 7-motion automatic transmission of Mercedes Benz. A maximum wear protection in every operating state is guaranteed.

Application instructions

RAVENOL ATF M-9 Serie was developed for use in the latest NAG2VSpport transmissions, 7G-Tronic (template 722.9 / W7A 700 / NAG2) without code A89, as well as for the 5-speed automatic transmissions (model 722.6 / W5A 580 / NAG1 and model 722.7 / FAG). It is also backward compatible for all earlier versions of Mercedes-Benz 4- and 5-speed automatic passenger car transmissions (template 722.3, 722.4, 722.5) with exception of the CVT automatic transmissions (continuously variable) template 722.8 installed in the A-Class W169 and in the B-Class W245, where RAVENOL CVT Fluid is required.

Characteristics

- a very good lubricating ability even at low temperatures in winter
- a high, stable viscosity index

- 1L | 1211108-001
- 4L | 1211108-004
- 10L | 1211108-010
- 20L | 1211108-020
- 20L | 1211108-B20
- 60L | 1211108-060
- 60L | 1211108-D60
- 208L | 1211108-208
- 208L | 1211108-D28
- 1000L | 1211108-700

- a very low pour point
- a very good oxidation stability
- protection against corrosion and foam formation
- good balanced coefficient of friction
- a high thermal and oxidative stability
- a excellent cooling capacity
- a excellent shear stability
- lowest evaporation losses
- a neutral behaviour against sealing materials
- a neutral behaviour because of inhibition against non ferrous metals

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		rot	VISUELL
Density at 20 °C	kg/m ³	846,0	EN ISO 12185
Pourpoint	°C	-48	DIN ISO 3016