



RAVENOL ATF 5/4 HP Fluid

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1212104

Oil type: Synthetic

Recommendations: Alfa Romeo 20HP 14891900, ATF LA 2634, ATF LT 71141, BMW 83229407765, BMW 83229407807, Citroën/Peugeot AL4 PR 9736.22, DTFR 13C110 (MB 236.11), Jaguar JLM 20237, Land Rover STC4863, MB 236.11, MB (A 001 989 22 03), Porsche 999.917.547.00, Renault DP0, VW TL 52162, VW/Audi G 052 162 A1, VW/Audi G 052 162 A2, VW/Audi G 052 162 A6, ZF S671 090 170

Application: Passenger car



RAVENOL ATF 5/4 HP Fluid is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission.

RAVENOL ATF 5/4 HP Fluid is ATF (Automatic Transmission Fluid) for all 4- and 5 speed automatic transmissions of ZF. It guarantees in any mode for maximum wear protection.

RAVENOL ATF 5/4 HP Fluid is natural brown colored.

Application instructions

RAVENOL ATF 5/4 HP Fluid is suitable for use in automatic transmission of ZF Serie 4 HP (4HP20, 4HP22, 4HP24) und 5HP (5HP18, 5HP19, 5HP24, 5HP30). Maintenance-filling under normal operating conditions.

Characteristics

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very good oxidation stability
- Protection against corrosion and foam formation
- Good balanced coefficient of friction
- A high thermal and oxidative stability
- An excellent cooling capacity

Technical Product Data

| CHARACTERISTICS | PROPERTY | DATA | AUDIT |
|------------------|-------------------|-----------|--------------|
| Colour | | gelbbraun | VISUELL |
| Density at 20 °C | kg/m ³ | 849,0 | EN ISO 12185 |
| Pourpoint | °C | -54 | DIN ISO 3016 |