



# RAVENOL Getriebeoel PSA SAE 75W-80



**Kategorie:** Gear oil for manual transmissions and drive axis

**Artikelnummer:** 1222100

**Viscosity:** 75W-80

**Specifications:** API GL-4

**Oil type:** Semi-synthetic

**Recommendations:** PSA B71 2315

**Application:** Passenger car

**RAVENOL Getriebeoel PSA SAE 75W-80** is a high-quality solvent refined base oil based semi-synthetic multi-grade transmission oil with special EP (extreme pressure) properties.

**RAVENOL Getriebeoel PSA SAE 75W-80** has a special formula for outstanding wear protection and lubrication properties.

## Application instructions

**RAVENOL Getriebeoel PSA SAE 75W-80** is used in manual shift transmissions requiring trouble-free lubrication.

**RAVENOL Getriebeoel PSA SAE 75W-80** can be used in manual transmissions where the manufacturer specifies a low-viscosity oil.

## Characteristics

- Outstanding oxidation protection.
- Low viscosity in low temperatures.
- Excellent wear protection.
- Enhanced EP properties.
- Good foaming properties.

- 1L | 1222100-001
- 4L | 1222100-004
- 10L | 1222100-010
- 20L | 1222100-020
- 20L | 1222100-B20
- 60L | 1222100-060
- 60L | 1222100-D60
- 208L | 1222100-208
- 208L | 1222100-D28
- 1000L | 1222100-700

- Neutral to sealants.
- Outstanding protection from rust and corrosion.

# Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		hellbgelb	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	8,5	DIN 51659-2
Viscosity at 40 °C	mm <sup>2</sup> /s	43,1	DIN 51659-2
Viscosity Index VI		178	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	52.500	ASTM D2983
Copper Strip Test at 121 °C		1b	ASTM D130
Density at 20 °C	kg/m <sup>3</sup>	843,0	EN ISO 12185
Flashpoint	°C	234	DIN EN ISO 2592
Pourpoint	°C	-39	DIN ISO 3016