



RAVENOL Super Synthetic Truck SAE 5W-30



Kategorie: Truck engine oil

Artikelnummer: 1121101

Viscosity: 5W-30

Specifications: ACEA E11, ACEA E6, ACEA E7, ACEA E8, ACEA E9, API CK-4, API SN

Oil type: Synthetic

Approvals: DTFR 15C110, DTFR 15C120, MAN M 3677

Recommendations: Cummins CES 20076, Cummins CES 20077, Cummins CES 20081, Cummins CES 20086, DAF Extended drain, Deutz DQC IV-10 LA, DTFR 15C100 (MB 228.31), JASO DH-2, Mack EO-O PP (Premium Plus), MAN M 3277, MAN M 3477, MB 226.9, MB 228.51, MTU Typ 3.1, Renault RXD, Renault VI RLD-3, Scania LDF, Scania LDF-4, VOLVO VDS-4

Application: Agricultural machinery, Truck

RAVENOL Super Synthetic Truck SAE 5W-30 is a synthetic, diesel saving "Low SAPS" lorry motor oil based on the latest additive technology, with very special base oils. It was developed specifically for diesel engines under extreme conditions for use in any season. Excellent for use in EURO 4, EURO 5 and EURO 6 engines along with low-sulphur diesel.

RAVENOL Super Synthetic Truck SAE 5W-30 is suitable for use in engines with or without particle filter and catalytic converter.

The cold viscosity SAE 5W ensures reliable cold starting in extreme temperatures (low cold-starting wear) and the quickest possible supply to all lubricating points. The high-temperature viscosity SAE 30 safely masters extreme stress. Friction loss and wear are reduced.

- 5L | 1121101-005
- 10L | 1121101-010
- 20L | 1121101-020
- 20L | 1121101-B20
- 60L | 1121101-060
- 60L | 1121101-D60
- 208L | 1121101-208
- 208L | 1121101-D28
- 1000L | 1121101-700

Application instructions

RAVENOL Super Synthetic Truck SAE 5W-30 is an all-season Low SAPS high performance commercial vehicle motor oil fine tuned for the new exhaust emission directives. All-season use in EURO IV, EURO V and EURO VI engines.

RAVENOL Super Synthetic Truck SAE 5W-30 is suitable for oil change intervals according to manufacturer specifications to over 100,000 km.

Characteristics

- Outstanding detergent properties, no residues in the engine
- Outstanding dispersing properties – prevents cold sludge and residue formation
- Extends the life of the particle filter by reducing the tendency to form particles
- Low sulphate ash-, phosphorus- and sulphur content "Low SAPS"
- Outstanding wear protection
- Outstanding oxidation stability
- Outstanding high temperature stability, high viscosity index
- Low fuel consumption for cost effectiveness
- Outstanding cold starting properties

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		braun	VISUELL
Sulphated Ash	%wt.	0,96	DIN 51575
tbn	mg KOH/g	10,8	ASTM D2896
Viscosity at 100 °C	mm ² /s	12,15	DIN 51659-2
Viscosity at 40 °C	mm ² /s	70,8	DIN 51659-2
Viscosity Index VI		170	DIN ISO 2909
CCS Viscosity at -35 °C	mPa*s	5530	ASTM D5293
Density at 20 °C	kg/m ³	849,0	EN ISO 12185
Flashpoint	°C	228	DIN EN ISO 2592
HTHS Viscosity at 150 °C	mPa*s	3,7	ASTM D5481
Low Temp. Pumping viscosity (MRV) at -40 °C	mPa*s	22.500	ASTM D4684
Noack Volatility	% M/M	9,1	ASTM D5800
Pourpoint	°C	-42	DIN ISO 3016