



RAVENOL Getriebeoel TGO SAE 75W-90 API GL 5



1L | 1222105-001
4L | 1222105-004
10L | 1222105-010
20L | 1222105-020
20L | 1222105-B20
60L | 1222105-060
60L | 1222105-D60
208L | 1222105-208
208L | 1222105-D28
1000L | 1222105-700

Kategorie: Gear oil for manual transmissions and drive axis

Artikelnummer: 1222105

Viscosity: 75W-90

Specifications: API GL-5, MIL -L-2105 D

Oil type: Semi-synthetic

Recommendations: CS 3000B, DTFR 12B100 (MB 235.0), DTFR 12B140 (MB 235.8), DTFR 13B100 (MB 235.1), Ford M2C-9002A, GM, Mack GO-G, MAN 342 M2 (160.000 km), MB 235.0, MB 235.1, MB 235.14, MB 235.8, MB 235.9, ZF TE-ML 05A, ZF TE-ML 07A, ZF TE-ML 16B, ZF TE-ML 16C, ZF TE-ML 16D, ZF TE-ML 17B, ZF TE-ML 19B, ZF TE-ML 21A

Application: Truck, Passenger car

RAVENOL Transmission Oil TGO SAE 75W-90 API GL 5 is a semi-synthetic transmission oil specifically for maximum duty hypoid geared transmissions.

RAVENOL Transmission Oil TGO SAE 75W-90 API GL 5 is designed based on high-quality solvent refined and synthetic base oils and specially harmonised additive treatment with extreme pressure (EP) active ingredients and other additives. This exceeds the needs of today's application requirements.

Application instructions

RAVENOL Transmission Oil TGO SAE 75W-90 API GL 5 is a maximum duty transmission oil for use in maximum duty, hypoid geared transmissions (axle drives, manual transmissions, etc.), where maximum duty transmission oils are required.

Characteristics

- Excellent oxidation stability
- Greatest possible protection from rust, corrosion, foaming
- Low solidification point
- Excellent extreme pressure (EP) properties
- High viscosity index
- Fuel savings

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelb	VISUELL
Viscosity at 100 °C	mm ² /s	15,7	DIN 51659-2
Viscosity at 40 °C	mm ² /s	97,3	DIN 51659-2
Viscosity Index VI		173	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	70.000	ASTM D2983
Copper Strip Test at 121 °C		1b	ASTM D130
Density at 20 °C	kg/m ³	842,0	EN ISO 12185
Flashpoint	°C	215	DIN EN ISO 2592
Pourpoint	°C	-45	DIN ISO 3016