



RAVENOL Getriebeoel LS SAE 75W-90



Kategorie: Gear oil for manual transmissions and drive axis

Artikelnummer: 1222102

Viscosity: 75W-90

Specifications: API GL-5 + LS, MIL -L-2105 D

Oil type: Synthetic

Recommendations: GM 1940058, GM 88862624, GM 88862625, GM 93165388, ZF TE-ML 05C, ZF TE-ML 05D

Application: Truck, Passenger car

RAVENOL Getriebeoel LS SAE 75W-90 is a synthetic lubricant for mechanical transmissions.

RAVENOL Getriebeoel LS SAE 75W-90 is designed based on high-quality solvent refined and synthetic base oils with special additive treatment and inhibition for higher stress on manual transmission oils and ensuring trouble-free transmission function.

1L | 1222102-001

4L | 1222102-004

10L | 1222102-010

20L | 1222102-020

20L | 1222102-B20

60L | 1222102-060

60L | 1222102-D60

208L | 1222102-208

208L | 1222102-D28

1000L | 1222102-700

Application instructions

RAVENOL Getriebeoel LS SAE 75W-90 was developed specifically for use in differential gear units with limited slip. It also ensures trouble-free lubrication in self-locking, hypoid geared transmissions.

Characteristics

- excellent oxidation stability
- excellent protection against rust and corrosion
- prevents foaming
- outstanding extreme pressure properties
- excellent limited slip properties

- fuel savings

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelb	VISUELL
Viscosity at 100 °C	mm ² /s	17,1	DIN 51659-2
Viscosity at 40 °C	mm ² /s	102,1	DIN 51659-2
Viscosity Index VI		182	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	84.300	ASTM D2983
Copper Strip Test at 121 °C		1b	ASTM D130
Density at 20 °C	kg/m ³	839,0	EN ISO 12185
Flashpoint	°C	210	DIN EN ISO 2592
Pourpoint	°C	-42	DIN ISO 3016