



RAVENOL VSE SAE 0W-20



Kategorie: Passenger car motor oil

Artikelnummer: 1111112

Viscosity: 0W-20

Specifications: ACEA C5

Oil type: Full synthetic

Approvals: Porsche C20, VW 508 00, VW 509 00

Recommendations: Ford WSS-M2C956-A1

Application: Passenger car

Technology: CleanSynto, USVO

RAVENOL VSE SAE 0W-20 is a PAO (Poly-alpha-olefin) based full synthetic low friction motor oil with especially USVO® and proven CleanSynto® technology for passenger car petrol and diesel engines with and without turbo-charging and direct injection.

Due to the USVO® technology we achieve an extremely high viscosity stability. We avoid the disadvantages of polymeric viscosity improvers while taking advantage of them. This improves engine protection, performance, engine cleanliness and oil drain intervals. The USVO® technology makes it possible that the product has no shear losses during the entire change interval and is extremely stable to oxidation. This unique technology helps oil lubricate faster, thereby minimizing friction while keeping the engine clean and efficient.

RAVENOL VSE SAE 0W-20 minimizes friction, wear and fuel consumption with excellent cold start characteristics.

RAVENOL VSE SAE 0W-20 has a high viscosity index because of its formulation with special base oils. The formulation contains chemical marker for identification and is green colored. The excellent cold start behavior ensures optimum lubrication safety during the cold running phase.

RAVENOL VSE SAE 0W-20 ensures compliance with the viscosity class even with a long oil life over the entire change interval.

By significantly reducing fuel consumption, **RAVENOL VSE SAE 0W-20** helps to protect the environment by reducing emissions.

Extended oil change intervals according to the manufacturer's instructions.

Application instructions

RAVENOL VSE SAE 0W-20 is universal fuel-economy engine oil, suitable for all modern passenger car gasoline and diesel engines where this grade of oil is recommended.

RAVENOL VSE SAE 0W-20 is specially developed for the latest Volkswagen Specification VW 508 00 / 509 00 (VW Blue Oil).

- 1L | 1111112-001
- 4L | 1111112-004
- 5L | 1111112-005
- 10L | 1111112-010
- 20L | 1111112-020
- 20L | 1111112-B20
- 60L | 1111112-060
- 60L | 1111112-D60
- 208L | 1111112-208
- 208L | 1111112-D28

Characteristics

- Guaranteed fastest possible lubrication of the engine.
- High fuel economy (FE) effect due to the base oils and additives used.
- Low volatilization tendency, thereby lower oil consumption.
- Provides protection against sludging, coking, varnish and corrosion even under unfavorable operating conditions.
- No oil-related deposits in combustion chambers in the piston ring zone and on valves.
- Lowered HTHS viscosity for maximum fuel economy.
- Stable engine oil, no NOx oxidation.
- Good soot absorption and dispersion.
- Neutral towards sealing materials.
- Contains chemical markers for identification and is green colored.

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		grün	VISUELL
Sulphated Ash	%wt.	0,77	DIN 51575
tbn	mg KOH/g	8,3	ASTM D2896
Viscosity at 100 °C	mm ² /s	8,3	DIN 51659-2
Viscosity at 40 °C	mm ² /s	45,3	DIN 51659-2
Viscosity Index VI		161	DIN ISO 2909
CCS Viscosity at -35 °C	mPa*s	4700	ASTM D5293
Density at 20 °C	kg/m ³	846,4	EN ISO 12185
Flashpoint	°C	240	DIN EN ISO 2592
HTHS Viscosity at 150 °C	mPa*s	2,73	ASTM D5481
Low Temp. Pumping viscosity (MRV) at -40 °C	mPa*s	10.900	ASTM D4684
Noack Volatility	% M/M	10,4	ASTM D5800
Pourpoint	°C	-60	DIN ISO 3016