



1L | 1213105-001
4L | 1213105-004
10L | 1213105-010
20L | 1213105-020
20L | 1213105-B20
60L | 1213105-060
60L | 1213105-D60
208L | 1213105-208
1000L | 1213105-700

- Reliable protection against wear, sludge, corrosion and adhesion.
- FZG test: Reaches failure load stage 12 before and after shearing.

RAVENOL ATF Fluid Type F

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1213105

Oil type: Mineral

Recommendations: Ford Motorcraft XT-1-QF, Ford Type M2C-33F, Ford Type M2C-33G, VOLVO 97330

Application: Oldtimer, Passenger car

RAVENOL ATF Fluid Type F is a universal ATF (automatic transmission fluid) for use as specialty transmission oil for Ford, BorgWarner and Volvo.

RAVENOL ATF Fluid Type F is designed based on refined base oils with a special additive treatment and inhibition ensuring trouble-free function.

Application instructions

RAVENOL ATF Fluid Type F is suitable for use as speciality transmission oil for Ford, Borg Wagner and Volvo.

Use **RAVENOL ATF Fluid Type F** according to aggregate manufacturer operating instructions in: Automatic transmissions, fluid turbo coupling, servo clutches and other hydrostatic and hydrodynamic systems.

Characteristics

- Universal use, therefore minimising the risk of confusion and making stock-keeping easy.
- Good lubricating ability even in low temperatures during winter.
- Stable lubricating film under extreme stress in midsummer resulting in comparatively low wear throughout the change interval.
- Excellent viscosity-temperature properties.
- High thermal resilience.
- Non-foaming even in extreme conditions.

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		rot	VISUELL
Viscosity at 100 °C	mm²/s	7,3	DIN 51659-2
Viscosity at 40 °C	mm²/s	34,3	DIN 51659-2
Viscosity Index VI		185	DIN ISO 2909
Density at 20 °C	kg/m³	848,0	EN ISO 12185
Flashpoint	°C	210	DIN EN ISO 2592
Pourpoint	°C	-45	DIN ISO 3016