



# RAVENOL ATF Fluid

**Kategorie:** Gear oil for automatic transmissions

**Artikelnummer:** 1213101

**Oil type:** Mineral

**Recommendations:** Allison C4, Caterpillar TO-2, DTFR 13C120 (MB 236.2), MAN 339 A, MB 236.2, Renk Doromat, Type A Suffix A (TASA)

**Application:** Oldtimer, Passenger car



**RAVENOL ATF Fluid** is designed on the basis of mineral refined base oils with a special additive and inhibition, which guarantee a perfect function.

**RAVENOL ATF Fluid** is a very high quality mineral gear fluid for automatic fluid couplings and torque converters as well as power steering aids.

## Application instructions

**RAVENOL ATF Fluid** should be used according to the instructions of the unit manufacturer in: Automatic transmissions, turbo couplings, servo clutches and other hydrostatic and hydrodynamic systems.

**RAVENOL ATF Fluid** must not be used if ATF Type DEXRON B or DEXRON D or ATF Type M2C-33 E / F / G are expressly mentioned as filling instructions.

## Characteristics

- Exceptionally good resistance to aging
- A very good viscosity-temperature behaviour
- Effective protection against wear
- Very good oxidation stability and low foaming tendency
- Enhanced protection against corrosion
- An extremely low pour point
- Compatible with all types of sealing materials
- Miscibility and compatibility with all brands of ATF's with Type A Suffix A specification

1L | 1213101-001

4L | 1213101-004

10L | 1213101-010

20L | 1213101-020

20L | 1213101-B20

60L | 1213101-060

208L | 1213101-208

1000L | 1213101-700

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		Rot	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	7,4	DIN 51659-2
Viscosity at 40 °C	mm <sup>2</sup> /s	34,6	DIN 51659-2
Viscosity Index VI		187	DIN ISO 2909
Density at 20 °C	kg/m <sup>3</sup>	848,0	EN ISO 12185
Flashpoint	°C	210	DIN EN ISO 2592
Pourpoint	°C	-48	DIN ISO 3016