



# RAVENOL ATF ULV D-M

**Kategorie:** Gear oil for automatic transmissions

**Artikelnummer:** 1212108

**Oil type:** Synthetic

**Recommendations:** AC Delco 10-4107, GM DEXRON® ULV ab/from 2017 GM 10L90, Ford 196825, Ford 2179795, Ford MERCON® ULV ab/from 2017 Ford 10R80, Ford Motorcraft XT-12-QULV, Ford WSS-M2C949-A, GM 19352619, VW G 060 540, VW G F53 006 M2, VW G F53 007 M4

**Application:** Passenger car



**RAVENOL ATF ULV D-M** is a Ultra Low Viscosity (ULV) Automatic Transmission Fluid (ATF), designed on the basis of PAO (Polyalphaolefin), Ester and highquality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission.

**RAVENOL ATF ULV D-M** is an ATF (Automatic Transmission Fluid) developed for the latest 6, 8 and 10 speed automatic transmissions from Ford and GM.

**RAVENOL ATF ULV D-M** guarantees maximum wear protection in all operating conditions and offers reduced fuel consumption.

## Application instructions

**RAVENOL ATF ULV D-M** was developed for use in 6, 8 and 10 speed automatic transmissions, especially from Ford and GM.

**RAVENOL ATF ULV D-M** is particularly suitable when the Ford WSS-M2C949-A specification is required.

It is recommended to flush with **RAVENOL ATF ULV D-M** before filling with **RAVENOL ATF ULV D-M**.

**RAVENOL ATF ULV D-M** is particularly suitable for

Ford 6-speed transmissions 6F15

Ford 8-speed automatic transmissions 8F24, 8F35, 8F40, 8F57

Ford 10-speed 10R60, 10R80-MHT, 10R80, 10R140

GM 10-speed 10L80 MF6, 10L90 MGL, 10L100 (Allison) MGM/MGU

Please observe the manufacturer's instructions and operating manual.

## Characteristics

- Very good lubricating properties also at low temperatures in winter
- Protection of highly loaded gear components, thus extended service life
- Very low flow point
- Excellent oxidation stability
- Protection against wear and corrosion

- 1L | 1212108-001
- 4L | 1212108-004
- 10L | 1212108-010
- 20L | 1212108-020
- 20L | 1212108-B20
- 60L | 1212108-060
- 60L | 1212108-D60
- 208L | 1212108-208
- 208L | 1212108-D28
- 1000L | 1212108-700

- Well balanced friction properties

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		rot	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	4,4	DIN 51659-2
Viscosity at 40 °C	mm <sup>2</sup> /s	18,6	DIN 51659-2
Viscosity Index VI		149	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	2970	ASTM D2983
Density at 20 °C	kg/m <sup>3</sup>	836	EN ISO 12185
Pourpoint	°C	-51	DIN ISO 3016