



RAVENOL HJC Concentrate Protect FL22



1.5L | 1410122-150
5L | 1410122-005
20L | 1410122-020
20L | 1410122-B20
60L | 1410122-060
208L | 1410122-208
1000L | 1410122-700

Kategorie: Radiator antifreeze

Artikelnummer: 1410122

Recommendations: Honda 08CLAG010S0 E Coolant, Ford VC-10-A2, Ford WSS-M97B55, Hyundai 00232-19010, Hyundai 07100-00200, Hyundai 07100-00400, Hyundai Long Life Coolant, Mazda 000077508E20, Mazda C100CL005A4X, Mazda C122CL005A4X, Mazda FL22 Coolant, Nissan Anti-freeze Coolant (L250), Nissan KE90299934, Nissan KE90299944, Subaru Coolant 16218, Suzuki Longlife Coolant

Application: Passenger car

RAVENOL HJC Hybrid Japanese Coolant Concentrate is an ethylene-glycol based, proven coolant without amines and silicates. The product is formulated as a long-term coolant based on a proven inhibitor development.

It is no longer just the anti-freeze effect (which automatically exists in an ethylene-glycol based product) which is critical for the quality of a coolant, but also the rust protection.

Therefore manufacturers subject coolants to long corrosion and cavitation tests.

RAVENOL HJC Hybrid Japanese Coolant Concentrate protects the cooling system from corrosion, frost, and in the summer from overheating.

Application instructions

RAVENOL HJC Hybrid Japanese Coolant Concentrate with frost and rust protection. Use according to the mixing chart. Follow manufacturer's

recommendations.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

Instructions: Clean cooling system, check for leaks, flush.

Mix **RAVENOL HJC Hybrid Japanese Coolant Concentrate** with distilled water (per mixing table) and add. Allow engine and heater to warm up, add coolant to fill level.

Table of mixing ratios

Antifreeze protection until	Parts Antifreeze	Parts Water
-20°C	35%	65%
-37°C	50%	50%
-50°C	60%	40%

Characteristics

- Excellent for light metal engines
- Good reserve alkalinity
- High-quality corrosion additives for optimal corrosion protection

- Elastomer compatible with elastomers used in automotive radiators

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		grün	VISUELL
Reserve alkalinity	ml0,1nHCl	min. 15	ASTM D1120
Boiling point	°C	>150	ASTM D1121
Water content	Gew. %	<5	ASTM D1123
Density at 20 °C	kg/m ³	1132,0	EN ISO 12185
Flashpoint	°C	>110	DIN 51758
Freezing point (50 % solution)	°C	-37	ASTM D1177
pH - value at 20 °C (50 Vol %)		7,0 - 8,5	ASTM D1287