



RAVENOL HVS High Viscosity Synto Oil SAE 10W-60



1L | 1115102-001

5L | 1115102-005

10L | 1115102-010

20L | 1115102-020

20L | 1115102-B20

60L | 1115102-060

208L | 1115102-208

208L | 1115102-D28

Kategorie: Passenger car motor oil

Artikelnummer: 1115102

Viscosity: 10W-60

Specifications: ACEA A3/B4, API CF, API SN

Oil type: Synthetic

Recommendations: MB 229.1

Application: Passenger car

RAVENOL HVS High Viscosity Synto Oil SAE 10W-60 is particularly recommended for high mileage vehicles from approx. 100,000 km. It is equally suitable for both petrol and diesel engines with or without a turbocharger and direct fuel injection.

RAVENOL HVS High Viscosity Synto Oil SAE 10W-60 is a newly developed synthetic motor oil with a unique formula, specially designed for high mileage vehicles.

Thanks to the additives in our **RAVENOL HVS High Viscosity Synto Oil SAE 10W-60**, which offer exceptional cleaning and maintenance for your engine, critical engine components are restored and seals are given extra protection. This means that the service life of vehicles can be extended, particularly in older, higher mileage vehicles.

RAVENOL HVS High Viscosity Synto Oil SAE 10W-60 has excellent lubricating film adhesion and high shear stability. Its engine-maintaining additives help to reduce oil consumption, offering protection against both sludge formation and wear and tear.

Application instructions

RAVENOL HVS High Viscosity Synto Oil SAE 10W-60 is ideal for year-round use in high mileage petrol and diesel engines which have covered 100,000 km or more and offers the additional benefit of keeping oil consumption low.

RAVENOL HVS High Viscosity Synto Oil SAE 10W-60 extends the service life of the engines of older vehicles by protecting against sludge formation and wear and tear, meaning lower oil consumption. Your engine is guaranteed to be exceptionally clean!

Characteristics

- High wear protection
- Fuel saving because of easy running characteristics
- Outstanding detergent and dispersant properties prevent sludge
- High oxidation stability for a long life
- Low vaporisation characteristics, therefore reduced oil consumption
- Brilliant cold cranking behaviour
- Excellent viscosity-temperature behaviour

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	22,1	DIN 51659-2
Viscosity at 40 °C	mm ² /s	155,6	DIN 51659-2
Viscosity Index VI		169	DIN ISO 2909
CCS Viscosity at -25 °C	mPa*s	5790	ASTM D5293
Density at 20 °C	kg/m ³	853,0	EN ISO 12185
Flashpoint	°C	248	DIN EN ISO 2592
Pourpoint	°C	-36	DIN ISO 3016